



Pasador cónico
con rosca interior

d	h10	6	8	10	12	14	16	20	25	30	40	50
a	≈	0,8	1,0	1,2	1,6	1,6	2,0	2,5	3,0	4,0	5,0	6,3
d ₂		M4	M5	M6	M8	M8	M10	M12	M16	M20	M20	M24
d ₃		4,3	5,3	6,4	8,4	8,4	10,5	13,0	17,0	21,0	21,0	25,0
t		6	8	10	12	12	16	18	24	30	30	36
t ₂	mín.	10	12	16	20	20	25	27	34	42	42	50
t ₃		1,0	1,2	1,2	1,2	1,2	1,5	1,5	2,0	2,0	2,0	2,5
l	js15	Peso (7,85 kg/dm ³) kg. cada 100 piezas ≈										
16		2,54										
20		3,70	6,2									
24		4,87	8,0	11,9								
28		6,02	9,8	14,7	17,9	27,0						
32		7,20	11,6	17,5	22,1	32,5	37,0					
36		8,35	12,5	20,4	26,3	38,0	44,0	68,0				
40		9,15	15,3	23,4	30,5	42,6	51,0	76,0				
45		10,5	17,7	26,8	35,5	50,4	60,0	89,0	115			
50		12,2	20,2	30,5	40,8	57,0	68,8	103	138			
55		14,0	22,8	34,3	46,2	64,2	77,5	116	160	185		
60			25,5	38,3	51,3	71,5	87,0	130	182	215		
70			31,0	46,5	62,5	85,8	104	158	225	275		
80			37,0	54,8	74,5	101	121	186	267	335		
90			43,2	63,3	86,5	116	139	216	310	395	800	
100				72,0	99,0	132	155	246	355	465	910	
110				80,5	121	148	172	276	400	525	1020	1580
120					133	164	199	306	445	590	1130	1750
130					145	180	217	337	490	660	1240	1910
140						195	235	370	540	725	1350	2100
150							253	402	610	785	1460	2270
165							279	450	660	890	1630	2530
180							305	500	740	990	1810	2790
200								565	840	1130	2050	3150
230								665	1000	1340	2310	3700
260								770	1160	1570	2770	4250

Modelo estándar en material **9SMnPb28K** en stock.

Rectificado con calibre por interferencia de la luz.

Suministrable también en material **100Cr6**, templado, en stock.