



Pasador cilíndrico con rosca interior

Forma: D, templado,
Material: Acero **100Cr6**
en stock en la
tolerancia m6.
Forma C, sin templar
en material
9SMnPb28K

d	m6 *	6	8	10	12	14	16	20	25	30	40	50	60	70	80
a ₁	≈	1,2	1,6	2,0	2,5	2,5	3,0	3,5	4,0	5,0	6,3	8,0	10,0	12,0	14,0
a ₂	≈	0,8	1,0	1,2	1,6	1,8	2,0	2,5	3,0	4,0	5,0	6,3	8,0	10,0	12,0
c ₁	≈	0,6	0,8	1,0	1,2	1,4	1,6	2,0	2,5	3,0	4,0	5,0	6,0	7,0	8,0
c ₂	≈	2,1	2,6	3,0	3,8	4,0	4,7	6,0	6,0	7,0	8,0	10,0	12,0	14,0	16,0
d ₂		M4	M5	M6	M6	M8	M8	M10	M16	M20	M20	M24	M30	M36	M42
d ₃		4,3	5,3	6,4	6,4	8,4	8,4	10,5	17,0	21,0	21,0	25,0	31,0	37,0	43,0
t ₁		6	8	10	10	12	12	16	24	30	30	36	40	54	63
t ₂	mín.	10	12	16	16	20	20	25	34	42	42	50	56	71	82
t ₃		1,0	1,2	1,2	1,2	1,2	1,5	1,5	2,0	2,0	2,5	2,5	3,2	4,0	5,0
l	js t5	Peso kg/1.000 piezas ≈ (calculado para d x l con 7,85 kg/dm ³)													
18		2,79													
20		3,67	6,40												
24		4,55	7,98	12,2											
28		5,43	9,56	14,7	19,5	28,2									
32		6,31	10,3	17,2	23,1	33,0	39,4								
36		7,19	11,9	19,7	26,7	37,8	45,7	67,8							
40		8,07	13,5	22,2	30,3	42,6	52,0	80,2							
45		9,17	15,5	25,3	35,1	48,7	59,9	92,6	131						
50		10,3	17,5	28,4	39,9	54,7	67,8	105	150						
55		11,4	19,5	31,5	44,7	60,7	75,7	117	169	237					
60		12,5	21,5	34,6	49,5	66,8	82,8	130	188	265					
70			25,5	40,8	59,1	78,9	98,5	155	226	320					
80			29,5	47,0	68,7	91,0	115	180	264	376					
90				53,2	78,3	103	131	205	303	431	754				
100				59,4	87,9	115	147	230	341	487	852				
110					97,5	127	163	255	380	542	951	1570			
120					107	139	180	280	418	598	1050	1720			
130						151	196	305	457	653	1150	1870	2620		
140						163	212	330	495	709	1250	2030	2840		
150							228	355	534	764	1350	2180	3060	4080	
160							244	380	572	820	1440	2340	3280	4380	
170								405	611	875	1540	2490	3510	4680	6010
180								430	649	931	1640	2650	3730	4980	6410
190								455	688	986	1740	2800	3950	5280	6800
200								480	726	1040	1840	2950	4170	5580	7200

* ADVERTENCIA: Otras zonas de tolerancia para forma D, p.e. d₆, h₈, k₆, por acuerdo. La zona de tolerancia deseada se ha de indicar en la designación, p.e. *Pasador DIN 7979 - D10 k6 x 40 - St*