


# ESPECIFICACIONES TECNICAS TORNILLERIA DE ALTA RESISTENCIA HOLO-KROME®

## Longitud de rosca - Tornillos de cabeza plana avellanada BSW



D	3/16	1/4	5/16	3/8	1/2	5/8	3/4
L	L1 en " min.						
1 1/4							
1 1/2	7/8						
1 3/4	7/8	1					
2	1	1	1 1/8				
2 1/4	1 1/8	1 1/8	1 1/8	1 1/4			
2 1/2	1 1/4	1 1/4	1 1/4	1 1/4	1 1/2		
2 3/4	1 3/8	1 3/8	1 3/8	1 3/8	1 1/2		
3	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2		2
3 1/4	1 5/8	1 5/8	1 5/8	1 5/8	1 5/8	1 3/4	2
3 1/2	1 3/4	1 3/4	1 3/4	1 3/4	1 3/4	1 3/4	2
4		2	2	2	2	2	2
4 1/2		2 1/4	2 1/4	2 1/4	2 1/4	2 1/4	2 1/4
5			2 1/2	2 1/2	2 1/2	2 1/2	2 1/2

## Longitud de rosca - Tornillos de cabeza plana avellanada UNC - UNF

D	N°4	N°5	N°6	N°8	N°10	1/4	5/16	3/8	7/16	1/2	5/8	3/4	7/8	1
L	L1 en " min.													
1														
1 1/4	3/4	3/4	3/4	7/8										
1 1/2	1	1	1	1 1/8	7/8									
1 3/4	3/4	3/4	3/4	7/8	1 1/8	1								
2					7/8	1 1/4	1 1/8							
2 1/4						1	1 3/8	1 1/4						
2 1/2						1 1/4	1 1/8	1 1/2	1 3/8	1 1/2				
2 3/4						1	1 3/8	1 1/4	1 5/8	1 3/4				
3						1 1/4	1 1/8	1 1/2	1 3/8	2				
3 1/4								1 1/4	1 5/8	1 1/2	1 3/4			
3 1/2								1 1/2	1 3/8	1 3/4	2	2	2 1/4	
3 3/4									1 5/8	2	2 1/4	2 1/4	2 1/2	
4									1 3/8	1 1/2	1 3/4	2 1/2	3	2 1/2
4 1/2										2	2 1/4	2	2 1/2	3
5										1 3/4	2	2 1/2	3	2 1/2