

ESPECIFICACIONES TECNICAS TORNILLERIA DE ALTA RESISTENCIA HOLO-KROME®

Conversión Fracciones / Milímetros

| Pulgadas | | mm | Pulgadas | | mm | Pulgadas | | mm |
|----------|-----------|-------|----------|-----------|-------|----------|-----------|--------|
| Fracción | Milesimal | | Fracción | Milesimal | | Fracción | Milesimal | |
| 1/64 | 0.016 | 0.40 | 33/64 | 0.516 | 13.10 | 1 | 1.000 | 25.40 |
| 1/32 | 0.031 | 0.79 | 17/32 | 0.531 | 13.49 | 1 1/8 | 1.125 | 28.58 |
| 3/64 | 0.047 | 1.19 | 35/64 | 0.547 | 13.89 | 1 1/4 | 1.250 | 31.75 |
| 1/16 | 0.063 | 1.59 | 9/16 | 0.563 | 14.29 | 1 3/8 | 1.375 | 34.93 |
| 5/64 | 0.078 | 1.98 | 37/64 | 0.578 | 14.68 | 1 1/2 | 1.500 | 38.10 |
| 3/32 | 0.094 | 2.38 | 19/32 | 0.594 | 15.08 | 1 5/8 | 1.625 | 41.28 |
| 7/64 | 0.109 | 2.78 | 39/64 | 0.609 | 15.48 | 1 3/4 | 1.750 | 44.45 |
| 1/8 | 0.125 | 3.18 | 5/8 | 0.625 | 15.88 | 1 7/8 | 1.875 | 47.63 |
| 9/64 | 0.141 | 3.57 | 41/64 | 0.641 | 16.27 | 2 | 2.000 | 50.80 |
| 5/32 | 0.156 | 3.97 | 21/32 | 0.656 | 16.67 | 2 1/4 | 2.250 | 57.15 |
| 11/64 | 0.172 | 4.37 | 43/64 | 0.672 | 17.07 | 2 1/2 | 2.500 | 63.50 |
| 3/16 | 0.188 | 4.76 | 11/16 | 0.688 | 17.46 | 2 3/4 | 2.750 | 69.85 |
| 13/64 | 0.203 | 5.16 | 45/64 | 0.703 | 17.86 | 3 | 3.000 | 76.20 |
| 7/32 | 0.219 | 5.56 | 23/32 | 0.719 | 18.26 | 3 1/4 | 3.250 | 82.55 |
| 15/64 | 0.234 | 5.95 | 47/64 | 0.734 | 18.65 | 3 1/2 | 3.500 | 88.90 |
| 1/4 | 0.250 | 6.35 | 3/4 | 0.750 | 19.05 | 3 3/4 | 3.750 | 95.25 |
| 17/64 | 0.266 | 6.75 | 49/64 | 0.766 | 19.45 | 4 | 4.000 | 101.60 |
| 9/32 | 0.281 | 7.14 | 25/32 | 0.781 | 19.84 | 4 1/4 | 4.250 | 107.95 |
| 19/64 | 0.297 | 7.54 | 51/64 | 0.797 | 20.24 | 4 1/2 | 4.500 | 114.30 |
| 5/16 | 0.313 | 7.94 | 13/16 | 0.813 | 20.64 | 4 3/4 | 4.750 | 120.65 |
| 21/64 | 0.328 | 8.33 | 53/64 | 0.828 | 21.03 | 5 | 5.000 | 127.00 |
| 11/32 | 0.344 | 8.73 | 27/32 | 0.844 | 21.43 | 5 1/4 | 5.250 | 133.35 |
| 23/64 | 0.359 | 9.13 | 55/64 | 0.859 | 21.83 | 5 1/2 | 5.500 | 139.70 |
| 3/8 | 0.375 | 9.53 | 7/8 | 0.875 | 22.23 | 5 3/4 | 5.750 | 146.05 |
| 25/64 | 0.391 | 9.92 | 57/64 | 0.891 | 22.62 | 6 | 6.000 | 152.40 |
| 13/32 | 0.406 | 10.32 | 29/32 | 0.906 | 23.02 | 7 | 7.000 | 177.80 |
| 27/64 | 0.422 | 10.72 | 59/64 | 0.921 | 23.42 | 8 | 8.000 | 203.20 |
| 7/16 | 0.438 | 11.11 | 15/16 | 0.938 | 23.81 | 9 | 9.000 | 228.60 |
| 29/64 | 0.453 | 11.51 | 61/64 | 0.953 | 24.21 | 10 | 10.000 | 254.00 |
| 15/32 | 0.469 | 11.91 | 31/32 | 0.969 | 24.61 | | | |
| 1/2 | 0.500 | 12.70 | 63/64 | 0.984 | 25.00 | | | |