













		Tipo	Referencia	A	B	C	D	E	F	Rosca	Longitud del espárrago	
Mando 8 Puntas Duroplasto acabado brillante												
		HEMBRA	I265	32	11	12	8	27		M6 M8	También disponible con agujero equivalente como estándar.	
		Inserto de aluminio	I266	44	13	14	8	29		M6 M8 M10		
			I267	57	18	18	11	40		M8 M10 M12		
			I268	70	18	22	12	43		M10 M12		
		MACHO	I265/M	32	11	12	8			M6	20 25 30	
		Espárrago cincado	I266/M	44	13	14	8			M8	20 25 30	
			I267/M	57	18	18	12			M10	25 30 40	
			I268/M	70	18	22	13			M12	40 50 60	
		HEMBRA PASANTE	I265/T	32	11	12	8		10 M6			
		Inserto de aluminio o latón	I266/T	44	13	14	8		13 M8			
			I267/T	57	18	18	12		16 M10			
			I268/T	70	18	22	13		18 M12			
Mando "SCA" Termoplástico acabado mate												
 		HEMBRA	2265	32	20	15	9			M5 M6		
		Inserto de latón	2266	44	21	17	11				M6 M8 M10	
			2267	57	27	20	11				M8 M10 M12	
 		MACHO	2265/M	32	20	15	9			M6	20 25 30	
		Espárrago cincado	2266/M	44	21	17	11				M8	20 25 30
			2267/M	57	27	20	11				M10	25 30