







Tipo	Referencia	A	B	C	D	E	F	Rosca	Longitud del espárrago
------	------------	---	---	---	---	---	---	-------	------------------------

Empuñadura "TL" Duroplasto acabado brillante



		HEMBRA	1345	60	30	20	18	12	25	M6 M8	
		Rosca moldeada	1346	80	30	22	18	12	30	M8 M10	
		1347	100	35	25	20	15	32	M10 M12		



Empuñadura "TCO" Termoplástico acabado mate - alta resistencia al impacto

		HEMBRA	3740	40	30	13	20	13		M5	
		Inserto de latón	3750	50	25	14	16	16		M5	
		3760	60	32	16	23	18		M6		
		3772	71	34	18	19	19		M6 M8 M10		
		3780	80	40	26	26	27		M10 M12		

		MACHO	3740/M	40	30	13	20	13		M5	15 20
		Espárrago cincado	3750/M	50	25	14	16	16		M5	15 20
		3760/M	60	32	16	23	18		M6	20 25	
		3772/M	71	34	18	19	19		M6 M8 M10	20 30	
		3780/M	80	40	26	26	27		M10 M12	30 40	

Empuñadura "TCV" Duroplasto acabado mate

		HEMBRA	1462	70	43	20	20	17		M6 M8 M10	
		Inserto de aluminio									

		MACHO	1462/M	70	43	20	20	17		M6 M8 M10	20 25
		Espárrago cincado									

OPCIONES ESPECIALES: Diámetros y longitudes no estándar, insertos y otras modificaciones son asequibles en cantidades mínimas.