


E4350-2

PATENTE REGISTRADA
PATENTS FILED



BREVETS DÉPOSÉS
PATENTE REGISTRADA



Anillas especiales para ganchos DIN 15401
Special master links for crane hooks DIN 15401
Maillon de tête spéciaux pour crochet DIN 15401
Argolão para ganchos DIN 15401

Grado 80

Grade 80

Grade 80

Grau 80

2 Ramales

2 Legs

2 Branches

2 Ramos

Capacidad según EN 818-4/DIN5688-3

W.L.L. according to EN 818-4/DIN5688-3

C.M.U. selon standard EN 818-4/DIN5688-3

Capacidade de acordo com EN 818-4/DIN5688-3

Conforme a la directiva europea 2006/42/CE

In accordance with the new european directive 2006/42/CE.

Conforme à la directive européenne machines 2006/42/CE.

Conforme a norma europeia 2006/42/CE.

ES EN FR PT

CMU Carga máxima de utilización

Working load limit

Charge maximale d'utilisation

Carga máxima de trabalho

T Tonelada

Tone

Tonne

Tonelada

Ref.	Ø Cadena	CMU	Nº Gancho Grúa	Dimensiones EN 1677-4						Kg.
				D	D1	P	P1	L	L1	
E4350-2-6-8	6	1,6 T	8	18	13	180	54	100	25	1,43
E4350-2-8-8	8	2,8 T	8	20	16	180	70	100	34	2,05
E4350-2-10-8	10	4,25 T	8	22	-	180	-	100	-	1,62
E4350-2-6-16	6	1,6 T	16	20	13	260	54	140	25	2,2
E4350-2-8-16	8	2,8 T	16	20	16	260	70	140	34	2,56
E4350-2-10-16	10	4,25 T	16	26	18	260	85	140	40	4,27
E4350-2-13-16	13	7,5 T	16	30	20	260	85	140	40	5,68
E4350-2-16-16	16	11,2 T	16	35	22	260	115	140	50	8,1
E4350-2-6-25	6	1,6 T	25	22	13	340	54	180	25	3,22
E4350-2-8-25	8	2,8 T	25	22	16	340	70	180	34	3,58
E4350-2-10-25	10	4,25 T	25	30	18	340	85	180	40	6,53
E4350-2-13-25	13	7,5 T	25	35	20	340	85	180	40	8,9
E4350-2-16-25	16	11,2 T	25	40	22	340	115	180	50	12,12
E4350-2-18-25	18	14 T	25	40	26	340	140	180	65	13,63

