

E8120

PATENTE REGISTRADA
PATENTS FILED



BREVETS DÉPOSÉS
PATENTE REGISTRADA



Eslinga de Elevación Tubular de alta calidad, 3 Ton poliéster ; Amarillo

Polyester high quality 3 ton yellow roundsling for lifting

Sangle ronde de levage de grande qualité 3 ton jaune en polyester

Banda de elevação redonda 3 ton amarela de alta qualidade de poliéster

Coefficiente de seguridad = 7

Safety factor = 7

Coefficient de sécurité = 7

Coefficiente de segurança = 7

Conforme la norma DIN EN 1492-1

Produced according to DIN EN 1492-1

Produites conformément à la norme DIN EN 1492-1

Fabricadas de acordo com a norma DIN EN 1492-1

Código de color según los estándares europeos

Color-Code according to European standard

Code colour en fonction des standards européens

Código de cores de acordo com as normas europeias

Conforme a la directiva europea 2006/42/CE

In accordance with the new european directive 2006/42/CE.

Conforme à la directive européenne machines 2006/42/CE.

Conforme a norma europeia 2006/42/CE.

ES EN FR PT

CMU Carga máxima de utilización

Working load limit

Charge maximale d'utilisation

Carga máxima de trabalho

T Tonelada

Tone

Tonne

Tonelada

Ref.	L mt	Circunferencia mt	CMU
E8120-3-2-1	1	2	30 T
E8120-3-3-1,5	1,5	3	30 T
E8120-3-4-2	2	4	30 T
E8120-3-5-2,5	2,5	5	30 T
E8120-3-6-3	3	6	30 T
E8120-3-8-4	4	8	30 T
E8120-3-10-5	5	10	30 T
E8120-3-12-6	6	12	30 T
E8120-3-16-8	8	16	30 T

