



### Empuñadura graduable hembra

Female indexed clamping handle  
Poignée débrayable taraudée  
Punho graduável fêmea



### Zamak, epoxi negro

Die cast zinc, black powder coated  
Zamak (zinc injecté) époxy noir  
Zamak, epóxi preto

### Material del inserto: Acero pavonado

Insert material: Black-oxide treated steel  
Insert: Taraudage en acier oxydation noire  
Material do inserto: Aço de oxidação negra

ES EN FR PT

#### P Gama preferida

Preferred range  
Gamme préférence  
Gama preferida

#### Gama estándar

Standard range  
Gamme standard  
Gama padrão

Temperatura de uso -30°C / +200°C

Working temperature  
Température d'emploi  
Temperaturas de utilização

Ref.		M	A	B	C	D
EGZ-43-4-N	●	M4	43	30	10	30
EGZ-43-5-N	●	M5	43	30	10	30
P EGZ-43-6-N	●	M6	43	30	10	30
EGZ-65-6-N	●	M6	65	34	14	45
P EGZ-65-8-N	●	M8	65	34	14	45
EGZ-65-10-N	●	M10	65	34	14	45
EGZ-80-8-N	●	M8	80	42	16	57
P EGZ-80-10-N	●	M10	80	42	16	57
P EGZ-80-12-N	●	M12	80	42	16	57
EGZ-94-12-N	●	M12	94	50	20	65
P EGZ-94-14-N	●	M14	94	50	20	65
EGZ-94-16-N	●	M16	94	50	20	65
EGZ-108-14-N	●	M14	108	56	23	75
P EGZ-108-16-N	●	M16	108	56	23	75
EGZ-108-18-N	●	M18	108	56	23	75



Otros colores de empuñaduras bajo consulta.

Other handle colors are available by request.

Autres couleurs sur demande.

Outras cores de punho, disponíveis sob consulta.

