



Caña roscada para pie Eco

Threaded rod for Eco feet
Tige filetée pour pieds Eco
Haste roscada para pé Eco

Acero inoxidable 304 (1.4301)

Stainless steel 304 (1.4301)
Acier inoxydable 304 (1.4301)
Aço inoxidável 304 (1.4301)

ES EN FR PT

Carga máxima (Kg)
Max. Load (kg)
Capacité de charge (kg)
Carga máxima (kg)

Llave Boca
Wrench
Clé
Chave de Boca

Otras medidas bajo consulta.
Other sizes on request.
Autres dimensions sur demande.
Outras medidas disponíveis sob consulta.

Ref.	MxL	K	MAX (kg)	Wrench	gr.
FCES-8-25	8x25	5,3	350	13	12
FCES-8-40	8x40	5,3	350	13	17
FCES-8-50	8x50	5,3	350	13	20
FCES-8-70	8x70	5,3	350	13	26
FCES-8-80	8x80	5,3	350	13	29
FCES-8-100	8x100	5,3	350	13	35
FCES-8-120	8x120	5,3	350	13	41
FCES-10-25	10x25	6,4	470	17	22
FCES-10-40	10x40	6,4	470	17	30
FCES-10-50	10x50	6,4	470	17	35
FCES-10-70	10x70	6,4	470	17	44
FCES-10-80	10x80	6,4	470	17	49
FCES-10-100	10x100	6,4	470	17	58

Ref.	MxL	K	MAX (kg)	Wrench	gr.
FCES-10-120	10x120	6,4	470	17	69
FCES-12-25	12x25	7,5	770	19	34
FCES-12-40	12x40	7,5	770	19	44
FCES-12-50	12x50	7,5	770	19	51
FCES-12-70	12x70	7,5	770	19	65
FCES-12-80	12x80	7,5	770	19	72
FCES-12-100	12x100	7,5	770	19	86
FCES-12-120	12x120	7,5	770	19	100
FCES-16-40	16x40	10	1.450	24	87
FCES-16-50	16x50	10	1.450	24	99
FCES-16-70	16x70	10	1.450	24	123
FCES-16-100	16x100	10	1.450	24	165
FCES-16-150	16x150	10	1.450	24	231

