



### Caña roscada para pie giratorio, rótula 22mm

Threaded rod for swivel feet, 22mm ball joint  
Tige filetée pour pied réglable, bille 22mm  
Haste roscada para pé giratório, rótula de 22mm

### Acero cincado

Zinc plated steel  
Acier zingué  
Aço zincado

ES EN FR PT

**Llave Boca**  
Wrench  
Clé  
Chave de Boca

**Carga máxima (Kg)**  
Max. Load (kg)  
Capacité de charge (kg)  
Carga máxima (kg)

Otras medidas bajo consulta.  
Other dimensions by request.  
Sur demande autres dimensions.  
Outras medidas disponíveis sob consulta.

Ref.	MxL	D		MAX (kg)	gr.
FCGA22-16-66	<b>M16x66</b>	22	22	1.450	112
FCGA22-16-100	<b>M16x100</b>	22	22	1.450	156
FCGA22-16-125	<b>M16x125</b>	22	22	1.450	190
FCGA22-16-150	<b>M16x150</b>	22	22	1.450	222
FCGA22-16-200	<b>M16x200</b>	22	22	1.450	285
FCGA22-20-85	<b>M20x85</b>	22	22	2.430	208
FCGA22-20-100	<b>M20x100</b>	22	22	2.430	237
FCGA22-20-125	<b>M20x125</b>	22	22	2.430	297
FCGA22-20-150	<b>M20x150</b>	22	22	2.430	341
FCGA22-20-200	<b>M20x200</b>	22	22	2.430	447
FCGA22-20-250	<b>M20x250</b>	22	22	2.430	551

Ref.	MxL	D		MAX (kg)	gr.
FCGA22-24-85	<b>M24x85</b>	22	24	3.610	293
FCGA22-24-100	<b>M24x100</b>	22	24	3.610	336
FCGA22-24-125	<b>M24x125</b>	22	24	3.610	408
FCGA22-24-150	<b>M24x150</b>	22	24	3.610	483
FCGA22-24-200	<b>M24x200</b>	22	24	3.610	633
FCGA22-24-250	<b>M24x250</b>	22	24	3.610	783
FCGA22-30-100	<b>M30x100</b>	22	24	5.770	512
FCGA22-30-150	<b>M30x150</b>	22	24	5.770	744
FCGA22-30-200	<b>M30x200</b>	22	24	5.770	976
FCGA22-30-250	<b>M30x250</b>	22	24	5.770	1.115
FCGA22-30-300	<b>M30x300</b>	22	24	5.770	1.420

